

Spesifikasi EX600

Display

Projection System	DLP Single 0.55" XGA
DMD type	DMD chip
Resolution	1024 x 768 pixels, 4:3
Brightness (ANSI lumens)	3,600 Lumens
Contrast Ratio (FOFO)	20,000:1
Display Color	1.07 Billion Colors
Native Aspect Ratio	Native 4:3 (5 aspect ratio selectable)
Light Source	Lamp 200W
Light Source life*	Normal 5000 hrs; Economic 10000 hrs; SmartEco 10000 hrs; LampSave 15000 hrs

Optical

Throw Ratio	1.96~2.15
Zoom Ratio	1.1X
Lens Control	Manual Focus
Lens shift	N/A
Projection Offset**	110±2.5%(Full-Height)
Projection Size	60"~180"
Keystone Correction	1D, Vertical +/- 40 degrees

Audio

Built-in Speaker	2W x1
------------------	-------

Special Feature

Security Feature	Security Bar Built-In smart system, BenQ Launcher, Hidden Wireless dingle, Bluetooth Audio out, Digital zoom(2x), Digital Shrink and Shift
------------------	--

Smart System

OS System	Android 6.0
ROM/RAM	16GB/2GB

Wireless

Wireless	Dual Band 802.11ac/b/g/n, 2.4G/5G
Bluetooth	4.0

Compatibility

Resolution Support	VGA(640 x 480) to WUXGA_RB(1920 x 1200)
Horizontal Frequency	15~102KHz
Vertical Scan Rate	23~120Hz
HDTV Compatibility	480i, 480p, 576i, 567p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM

Power

Power Consumption(Max/Normal/Eco)	Max 320W. Normal 280 W. Eco 235 W.
Standby Power Consumption	Normal < 0.5W
Power Supply	100 ~ 240V AC

Dimension and Weight

Net Weight (Kg/ lbs)	2.5 Kg
Dimensions (W x H x D)(mm)	296 x 120 x 232 mm

Operation Condition

Noise Level(Normal/Eco)	33/29 dBA
Operating Temperature	0 ~ 40oC

Accessories (Standard)

Remote Control w/ Battery	Yes(RCI023)
Power Cord (by region)	Yes
Warranty Card (by region)	Yes
VGA cable	Yes

QSG	Yes
Wireless Dongle	WDR02U

Accessories (Optional)

Spare Lamp Kit	Yes (5J.JLR05.001)
Universal Ceiling Mount	Yes
3D Glasses	Yes

OSD

OSD Language	Arabic/Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hindi/ Hungarian/ Italian/ Indonesian/Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/ Spanish/ Swedish/ Turkish/Thai/TraditionalChinese/Vietnamese /Farsi (30 Languages)
--------------	--

- * Kontras diukur dengan standar sepenuhnya terbuka dan tertutup.
- * Hasil LightSource akan bervariasi tergantung pada kondisi lingkungan dan penggunaan. Fitur dan spesifikasi produk yang sebenarnya dapat berubah tanpa pemberitahuan.
- * Penyimpanan: Suhu: -20 ~ 60 ° C; Kelembaban: 10 ~ 90% RH (tanpa kondensasi)
- * Kualitas transmisi tergantung pada lingkungan Wi-Fi dan kompatibilitas pencerminan layar perangkat dari berbagai merek.